



SITOR cylindrical fuse link, 10 x 38 mm, 6 A, aR, Un AC: 600 V, Un DC: 700 V, DC according to UL

Model	
product brand name	SETRON
product designation	SITOR cylindrical fuse link
design of the product	DC acc. to UL
General technical data	
operating class of the fuse link	aR
size of the fuse link	10x38 mm
type of voltage / of the operating voltage	AC
supply voltage / at DC	700 V
operating voltage / rated value	600 V
Dissipation	
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	1.5 W
operational current / at AC / rated value	6 A
Main circuit	
operational current / rated value	6 A
Product details	
product component / striker	No
Mechanical Design	
mounting position	Any, preferably vertical
net weight	9 g
General Product Approval	
Declaration of Conformity	



[Miscellaneous](#)



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC1006>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC1006>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC1006

